



- A:Material:
 1. Insulator: High temperature thermoplastic
 UL94V-0 (BLACK LCP)
 2. Pico: Bronze Plating,
 50U" MIN NICKEL UNDERPLATED,
 3-8U" GOLD ON THE CONTACT AREA,
 100U" TIN PLATING ON SOLDER TAIL
 B:Electrical specifications:
 Voltage rating: 10 V AC
 Current rating: 0.5A
 Dielectric strength: 500V AC for 1
 minute min.
 Insulation resistance: 1000 M ohm
 Contact resistance: 100 milliohm max
 Operation temperature: -25°C to +95°C
 Product withstanding rff low
 soldering 260°C for 10s
 C:Mechanical specifications:
 3.1 Durability: 5000 cycles

XKSIM-011B-P8-X

RECOMMENDED PCB PATTERN DIM.
 TOLERANCE : ±0.05

AWith
 Bwith

NO	DATE	DESCRIPTION OF REVISION	DESIGNED	CHECKED	APPROVED	MATERIAL		SPECIFICATION		FINISH	QUANTITY	SCALE
번호	변경일자	변경 내용	작성	검토	승인	DESIGNED	CHECKED	APPROVAL	DRAWING NUMBER	표면처리	수량	척도
						작성	검토	승인	도번			UNIT 단위
						김도현	박재규	최국홍	PART NAME			mm
						김도현	박재규	최국홍	부품명			
									MODEL NAME			
									제품명			
DESIGNED						삼원전자 주식회사			3RD ANGLE PROJ	HANYONES TECH CO.,LTD		FILE NO.
작성										한유안 ELECTRONICS CO.,LTD		